

Boost Speed, Save Space and Lower Energy Consumption With Xccela Flash Memory



Xccela™ flash memory sets a new record for NOR flash speeds to meet the demand for instant-on performance and fast system responsiveness in automotive, industrial, consumer and networking applications.

With **Xccela** flash, system designers no longer have to choose between the performance of parallel NOR and the small footprint of serial NOR. Our **Xccela** flash uses a new interface with as few as 11 active signals. It delivers 5X performance while reducing pin count by 4X, energy consumption by 3X and package size by 2X compared to the page mode parallel NOR solution. In addition to enabling one of the fastest possible direct code execution and shadowing, **Xccela** flash paves the way for simpler system designs, lower system costs and lower energy consumption.

Key Features and Benefits

- **Densities:** 256Mb to 2Gb
- **Performance:** Up to 200 MHz in double data rate (DDR) with data strobe, 400 MB/s read throughput or 166 MHz in single transfer rate, 166 MB/s read throughput, 73.3ns initial access time and 2.5ns subsequent access time, 2 MB/s (256 bytes page buffer) program throughput
- **Interface:** Standard single SPI interface and octal I/O interface, along with DDR mode, to enable a high degree of flexibility, performance and backward compatibility; only 11 active signals for DDR operation
- **Single Supply Voltage:** Low-voltage range (1.7–2.0V) or full voltage range (2.7–3.6V) support
- **Energy Consumption:** Low 28 pJ/bit energy consumption
- **Package Options:** Industry-standard, Pb-free TBGA24
- **Temperature Range:** Full industrial (–40°C to 85°C) and automotive AEC-Q 100 Grade 2/Grade 1 (–40°C to 105°C/125°C) temperature support to address a variety of applications
- **Security*:** Hardware and software block protection; one-time programmable region

Why Buy Micron Xccela Flash Memory?

1. Expertise and Quality

Products defined and developed by a team of engineers, system architects and ecosystem partners to give you access to leading, proven, high-reliability solutions that can handle the most stringent application requirements.

2. Competitive Solutions

Get instant power-on with best-in-class 400 MB/s read throughput; improve firmware updates with extremely fast 2 MB/s program throughput; and increase application security* with features like advanced block protection.

3. Unwavering Commitment to the Industrial and Automotive Markets

Micron is expanding its Manassas, U.S. fabrication site to support the rapidly growing need for high-quality, high-reliability memory solutions. This site manufactures our long-lifecycle products to ensure supply continuity for the industrial and automotive markets. Delivering a leading-edge, state-of-the-art auto- and industrial-qualified memory portfolio with the associated lifecycle support places Micron in a class by itself and further underscores our continued commitment to these markets.



Micron Xccela Flash Memory

Performance That Matters

Serial peripheral interface (SPI) NOR flash is used in a wide array of applications for boot code, program code and data storage. **Xccela** flash memory maintains backward compatibility with SPI NOR flash, making migration between these products relatively easy. **Xccela** flash also offers dramatically better performance while consuming less energy per bit compared to traditional SPI and quad SPI NOR flash, with random access times as fast as 83ns and sequential byte reads as fast as 2.5ns. Sustained read throughputs of 400 MB/s enable an entire 1Gb **Xccela** flash device to be read in a mere 0.3 seconds. With **Xccela** flash memory's direct execute-in-place operation and low-pin-count interface, valuable board space can be saved and the need for code shadowing can be eliminated.

Xccela Flash Applications

With lower-density memory subsystem interfaces trending toward x4/x8 SPI interfaces and performance growing exponentially, OEMs are looking for simple, low-energy memory solutions to meet their needs.

- **Automotive:** Based on advanced NOR process technology and robust design methodologies, **Xccela** flash memory is highly reliable, supports the automotive temperature range, and is AEC-Q100 qualified. With automotive systems integrating electronic technology

at lightening-quick speeds, consumer expectations for instant-on has carried over to automotive applications such as advanced driver assistance systems, infotainment platforms and instrument clusters. **Xccela** flash is ideal for instant-on applications.

- **Industrial Multi-Market:** As low-end microcontrollers (MCUs) continue to shrink in die size, there is a need to augment the small amount of internal memory with a low pin count, high-performance memory subsystem. With only 11 active signal pins, **Xccela** flash significantly reduces the bond pads of an MCU design. Other industrial human machine interface applications that require instant-on and fast execution like industrial PCs, factory automation and medical diagnostic equipment can also benefit from **Xccela** flash.
- **Core Networking:** Enterprise communication demands fast, robust and secure networking equipment. **Xccela** flash breaks the NOR flash speed limit and addresses the requirements of next-generation networking infrastructures.
- **Consumer:** The combination of extreme performance and low pin count makes **Xccela** flash ideal for consumer applications that are space-constrained and require instant-on, such as digital still cameras, DSLRs and home automation.

Serial NOR Flash Product Family

Product Family	Voltage Range	Sector Erase Size	Bus Width	Density Range ¹	Max Clock/ Max Data Transfer Rate	Package ¹
Xccela Flash/MT35X	1.7–2.0V, 2.7–3.6V	Uniform 4KB, 32KB, 128KB	x1, x8	256Mb–2Gb	200 MHz DDR (400 MB/s)	BGA
MT25T	2.7–3.6V	Uniform 4KB, 32KB, 64KB	x1, x2, x4, x8	256Mb–1Gb	166 MHz (166 MB/s)	BGA
MT25Q	1.7–2.0V, 2.7–3.6V	Uniform 4KB, 32KB, 64KB	x1, x2, x4	128Mb–2Gb	166 MHz (83 MB/s)	DFN, BGA, KGD, CSP
MT28EW	1.65–3.6V	Uniform 128KB	x8, x16	128Mb–1Gb	95ns, 20ns page	TSOP, BGA
MT28FW	1.65–3.6V	Uniform 128KB	x16	512Mb–2Gb ²	105ns, 20ns page	TSOP, BGA

¹. Not all densities available in all package and voltage combinations.
². Stacked solution.

micron.com

*No hardware, software or system can provide absolute security under all conditions. Micron assumes no liability for lost, stolen or corrupted data arising from the use of any Micron products, including those products that incorporate any of the mentioned security features. Products are warranted only to meet Micron's production data sheet specifications. Products, programs and specifications are subject to change without notice. Dates are estimates only. ©2016 Micron Technology, Inc. All rights reserved. All information is provided on an "AS IS" basis without warranties of any kind. Micron, the Micron logo, Xccela and all other Micron trademarks are trademarks of Micron Technology, Inc. All other trademarks are the property of their respective owners. Rev. J 1/19 CCMMMD-676576390-10244

